

# 60° Glossmeter

## ■ Introduction:

BEVS1501U is a newly upgraded 60° glossmeter from the original BEVS1501, manufactured according to ISO 2813, ASTM D2457, GB/T 9754, GB/T 9966 and GB/T 13891 standards.

## ■ Technical info:

- ◆ Reading range : 0 - 199.9 GU
- ◆ Indication error:  $<\pm 1.2$  GU
- ◆ Stability:  $\pm 0.4$  GU / 30 Mins
- ◆ Measuring area: 14×30 mm
- ◆ Dimension: 122×40×105 mm (L×W×H)
- ◆ Power supply: 1.5 V



## ■ Features:

- ◆ Handy and portable
- ◆ Single battery can be used for a long time
- ◆ Long-life light source and good stability



## ■ Application:

- ◆ Furniture, electrical appliances, automobiles and other industries: ink, paint, baking varnish, coating, wood products, leather products and other surface gloss
- ◆ Building decoration industry: surface gloss measurement of marble, granite, vitrified polished tiles, ceramic tiles, floors, etc.
- ◆ Printing and packaging industry: surface gloss measurement of plastics, paper, etc.
- ◆ Measurement of surface gloss of other objects

## ■ Order info:

BEVS 1501U 60°Glossmeter